

FIG. 1 (PRIOR ART)




FIG. 2




FIG. 3




FIG. 4




FIG. 5







FIG. 6



**FIG. 7A**



**FIG. 7B**



T08090"05T92850

FIG. 8

22-3






FIG. 9




FIG. 10




FIG. 11A





FIG. 11B






FIG. 13




FIG. 14




FIG. 15




FIG. 16






FIG. 17

Frame Rate : 60 Hz 24-bit-Color

	With Blank		Active		Pixel Clock	TMDS GVIF 30b		HSGI-4L	
	Pixel	Line	Pixel	Line		4ch	1ch	kbps	Gbps
SVGA	1056	628	800	600	40	0.40	1.20	578	0.35
XGA	1344	806	1024	768	65	0.65	1.95	739	0.57
SXGA	1696	1066	1280	1024	108	1.08	2.43	924	0.95
UXGA	2160	1250	1600	1200	162	1.62	3.54	1,154	1.39
HDTV	2592	1124	1920	1080	175	1.75	3.84	1,385	1.50
QXGA	2768	1598	2048	1536	265	2.65	5.79	1,477	2.27

TMDS : Transition Minimized Differential Signal  
 GVIF : Gigabit Video Interface  
 HSGI-4L : 4-bit Packet Line (PRESENT INVENTION)